

TECHNICAL DATA SHEET

Novatik NATURA | ROMAN

With its warm colours, smooth slopes and broad curves, Novatik NATURA ROMAN perfectly captures the ageless appeal of sunbaked Mediterranean roofs, but unlike traditional terracotta tiles our Novatik NATURA ROMAN panels are lightweight and immensely strong. Novatik NATURA ROMAN tiles are produced using premium quality steel, protected with ZnMg 250 g/sqm alloy plus additional multiface® anti-corrosion protection on both sides, and covered with natural volcanic stone chips. The multiface® protective layer represents a high-performance treatment applied to steel, with a thickness of 1 to 2 microns, and is an almost invisible (thin organic coating) sealant applied to hot-dip galvanized steel strips (ZnMg). Its remarkable properties give the steel a durable premium sealing, with excellent corrosion resistance and superior adhesion of subsequent finishing layers.

TRANSPARENT ACRYLIC COATING

TEXTURED FINISH
(VOLCANIC ROCK CHIPS)

BASE LAYER / COAT

MULTIFACE® PRIMER

PROTECTIVE LAYER ZN-MG

STEEL

PROTECTIVE LAYER ZN-MG

MULTIFACE® PRIMER



COLOURS:



TECHNICAL INFORMATION

TOTAL LENGTH	1320 mm
LENGTH OF COVER	1270 mm
WIDTH OF COVER	370 mm
TILES / SQM	2.15 modules / sqm
ROOF PITCH	Min. 16°
WEIGHT / SQM	7.00 kg / sqm
BATTEN SPACING	370 mm
STEEL TYPE / STEEL THICKNESS	DX51 / 0.45 mm
CORROSION RESISTANCE	Protective Layer ZnMg 250 g/sqm + multiface® anti-corrosion protection
TEXTURED FINISHED	Acrylic resin + Volcanic rock (Basalt) + Protective layer
TOTAL MAXIMUM THICKNESS	2.1 mm

Manufactured by: NOVATIK SRL

HEAD QUARTERS: 9 Mai street, no. 75, Băicoi, Prahova, Tel: +40 244 260 140; Fax: +40 244 260 145; office@novatik.ro, novatik.ro
Novatik NATURA ROMAN Technical Data Sheet – ENG_V3 | May 2023