TECHNICAL DATA SHEET

Novatik NATURA | SI AT

All the appearance of natural slates, combined with the strength of steel and the weather resistance of a rock chip coating, this minimalist design is an ideal choice for those seeking a more modern look. With its flat profile and neutral colour, NATURA SLATE is suitable for both vertical and pitched roofs, perfectly meeting the needs of contemporary architectural design.

Novatik NATURA SLATE tiles are produced using premium quality steel, protected with ZnMg 250 g/sqm alloy plus additional multiface® anti-corrosion protection on both sides, and covered with natural volcanic stone chips. The multiface® protective layer represents a high-performance treatment applied to steel, with a thickness of 1 to 2 microns, and is an almost invisible (thin organic coating) sealant applied to hot-dip galvanized steel strips (ZnMg). Its remarkable properties give the steel a durable premium sealing, with excellent corrosion resistance and superior adhesion of subsequent finishing layers.

TRANSPARENT ACRYLIC COATING

TEXTURED FINISH (VOLCANIC ROCK CHIPS)

BASE LAYER / COAT MULTIFACE® PRIMER PROTECTIVE LAYER ZN-MG STEEL PROTECTIVE LAYER ZN-MG MULTIFACE® PRIMER

30

YEARS

AESTHETIC

WARRANTY





COLOURS:



TECHNICAL INFORMATION

TOTAL LENGTH	1280 mm
LENGTH OF COVER	1225mm
WIDTH OF COVER	370 mm
TILES / SQM	2.17 modules/sqm
ROOF PITCH	Min. 16°
WEIGHT / SQM	aprox. 6.70 kg/sqm
BATTEN SPACING	370 mm
STEEL TYPE / STEEL THICKNESS	DX51 / 0.45 mm
CORROSION RESISTANCE	Protective Layer ZnMg 250 g/sqm +
	multiface® anti-corrosion protection
TEXTURED FINISHED	Acrylic resin +
	Volcanic rock (Basalt) +
	Protective layer
TOTAL MAXIMUM THICKNESS	2.1 mm

Manufactured by: NOVATIK SRL

HEAD QUARTERS: 9 Mai street, no. 75, Băicoi, Prahova, Tel: +40 244 260 140; Fax: +40 244 260 145; office@novatik.ro, novatik.ro Novatik NATURA SLATE Technical Data Sheet - ENG_V2 | January 2023